



***For all of your
conveyor needs!***

***Gravity Roller
Gravity Wheel
Line Shaft
Chain Driven Live
Roller
Belt Conveyor
Belt Driven Live Roller
Conveyor Accessories
Electrical Control
-Systems
Sortation Equipment***

**Metzgar Conveyor
Company**

901 Metzgar Drive NW
Comstock Park, MI 49321

Phone: 616-784-0930

Fax: 616-784-4100

Toll Free: 888-266-8390

www.metzgarconveyors.com

E Mail

sales@metzgarconveyors.com

“Sortation Devices”

Sortation Devices

Precisely timed sortation devices to sort and divert products with tote and carton weights ranging from 1 oz. to 60 pounds at rates from 1 per minute to 60 per minute. Designed to adapt to belt and roller conveyors. Sorting accuracy is unequalled, while maintaining safe product handling and

M 45- Pivoting Bow Arm Sorter

Designed to handle both totes and cartons up to 60 pounds in weight
Eliminates high decibel readings that develop when handling plastic totes on straight diverter arms. This is accomplished through the unique "bowed" arm design and dog bone wear strip face
Capable of sorting individual items at rates up to 50 per minute or maintain an "out" position for the constant flow of slugs
Adaptable to both belt and roller conveyors at sortation angles of 30 and 45 degrees
Right hand or left hand diverts available



M 60 – Pivoting Divert Sorter



Positive high-speed sortation at rates up to 60 cases per minute and weights up to 65 pounds
Gentle handling of fragile items, including china and crystal
Maintains proper carton orientation
Proven reliability when used with high-speed sortation belt units
Right hand or left hand diverts available
Minimal maintenance requirements
"Positive sortation"
Optional air assist feature available for sorting lightweight or bagged items

M 50/50 – Right Angle Pusher

All items are pushed off at right angles with the same CONSTANT FORCE AND SPEED - NO LAUNCHINGS
Unequalled in its ability to handle totes and cartons at rates up to 60 cycles per minute
Compact and space efficient with a unique telescoping design; this unit requires a VERY SMALL SPACE on the side of the conveyor for mounting purposes.
Adaptable to belt and roller conveyors
Can be easily modified to accommodate special applications

