



*For all of your
conveyor needs!*

*Gravity Roller
Gravity Wheel
Line Shaft
Chain Driven Live
Roller
Belt Conveyor
Belt Driven Live Roller
Conveyor Accessories
Electrical Control
-Systems
Sortation Equipment*

**Metzgar Conveyor
Company**

901 Metzgar Drive NW
Comstock Park, MI 49321

Phone: 616-784-0930

Fax: 616-784-4100

Toll Free: 888-266-8390

www.metzgarconveyors.com

E Mail

sales@metzgarconveyors.com



“Model 440 Series LineShaft Conveyor”



Conveyor Features

Metzgar 440 Series Lineshaft conveyor is commonly used for conveying corrugated boxes or totes. The 440 Series is ideally suited for applications involving warehousing or manufacturing.

440 Series

Rollers: 1.9" diameter x 16 gage galvanized tube with 7/16" hex axle with Ball bearings.

Roller ends have swaged press bearings to provide a smooth carrying surface.

Roller grooves are cold formed in the roller shell.

Roller axles are 7/16" hex stock spring loaded for easy removal and assembly.

The top of the roller is 5/16" above the top flange of the frame.

Standard roller centers are available in 2-1/4", 3", 4-1/2" and 6"

Frame: 10 gage formed channel 4-1/2" deep with 1-1/4" flanges.

Axle holes are 7/16" hex punched on 1-1/2" centers.

Crossmembers are formed 10 gage steel bolted to frames.

Drive Belts: 3/16" diameter x 83A durometer.

Drive Shaft: 1" diameter 1045 CRS to specific size tolerance.

Finish: Standard finish for painted components is Metzgar Medium Blue or Vista Green